

LCD Video Wall Series



As a professional construction team, with 30+ years experience in video processing and case practicing, we will provide our customers with quality products, customized professional large-screen display system solutions.

Industry
A+ SCREEN

HD

3D
Noise
reduction

24H
Continuous
Operation

178°
VIEW
ANGLE

>60000
HOURS
Life

LCD Video Wall General Parameters

Item	46" LED backlight	46" (CCFL)	47" LED backlight	55" LED backlight	60" LED backlight
Size (mm)	1023.9×578.5	1025.6×579.8	1046.8×591.6	1215.0×686.0	1335.9×754.2
Image aspect ratio	16:9				
Bezel(mm)	5.7	6.7	4.9	5.5	6.3
Brightness (cd/m)	700/500	700/450	800/500	700/500	700/500
Resolution	1920×1080	1366×768	1920×1080	1920×1080	1366×768
Viewing angle	178°	178°	178°	178°	178°
Response time	5ms				
Color	16.7M	16.7M	10.6M	16.7M	16.7M
Power supply	100~240V	100~240V	100~240V	100~240V	100~240V
Power consumption	200W/160W	350W/250W	200W/160W	260W/220W	450W/350W
Input interfaces	Digital input	DVI			1
		HDMI			1
	Analog input	VGA			1
		YPrPb			3BNC
		CVBS			1BNC
Output interfaces	Digital output	DVI			1
		VGA			1
	Analog output	YPrPb			3BNC
		CVBS			1
	Control interface	RS485 (RJ45)			Looping